

# Cylinder brushes up to l = 1,200 mm

Cylinder brushes up to a maximum length of 1,200 mm and a maximum overall diameter of 400 mm.



GUTMANN QUALITY for a longer service life, best performance and high economic efficiency.

## Highlights

- Extremely smooth running due to balanced body design and highest production quality
- Optimal cleaning performance due to high line load
- Suitable for high speeds (up to 1,000 rpm)
- Long service life due to high-quality fill types

## Anwendungsbereiche

- Wet scrubbing
- Scrubber dryers
- Hard floor cleaning machines (incl. tiles and safety floors)
- Carpet cleaning machines
- Escalator cleaning

## Technical data

Overall dimension	
Length/Width/Height	≤ 1200 mm / - / -
Diameter	≤ 400 mm
Body	
Diameter	≤ 250 mm
Wall thickness	6 – 20
Material	Solid rods, hollow rods or injection-moulded bodies made of all common thermoplastics, such as PP polypropylenes, PE polyethylenes, PS polystyrenes, ABS acrylonitrile-butadiene-styrene copolymers, PA polyamides, POM polyoxymethylenes/polyacetals and wood composites
Colours	All basic colours, as well as many common colors, special colours possible
Fill	
Fill Materials	PP, PA6, PA6.6, PA6.10, PA6.12, PET, PBT, antistatic materials, conductive synthetic fibres, abrasive synthetic fibres (filled with SiC, aluminum oxide Al <sub>2</sub> O <sub>3</sub> or diamond), variety of animal hair and bristles as well as plant fibres, wire bristles (brass, steel)
Density of brush pattern	Light, medium, dense
Brush pattern	Linear, spiral, single-row, double-row, chevron, W-shaped, double helix, zig-zag, segmented
Properties	Very soft, soft, medium, hard, abrasive
Colours	All common colours, special colours possible
Connection	
Connection	Integrated bearing, external bearing, positive drive, belt drive, internal drive